

## ◆ Specifications and Technical Data

Model	KC-30H	KC-35H	KC-45H
Cooling Capacity (BTU/HR)	9500/9700	11400/11600	17600/18000
Heating Capacity (BTU/HR)	8300/8500	10100/10500	16500/17000
Electric Heat (BTU/HR)	8500/10700	8500/10700	8600/10700
Rated Voltage	208/230V~	208/230V~	208/230V~
Rated Frequency	60Hz	60Hz	60Hz
Design Pressure Lowside	150 P.S.I.	150 P.S.I.	150 P.S.I.
Design Pressure Highside	330 P.S.I.	380 P.S.I.	340 P.S.I.
Cooling AMPS	4.8/4.6	5.9/5.5	9.7/8.9
Cooling Watts	970/990	1210/1235	1955/2000
Cooling EER	9.8	9.4	9.0
Heating AMPS	4.5/4.2	5.8/5.1	8.8/8.3
Heating Watts	850/870	1100/1140	1790/1850
Heating EER	9.8	9.2	9.2
Electric Heat AMPS	15.6/16	15.6/16	15.6/16
Electric Heat Watts	3500	3500	3600
Air Flow Volume (CFM)	310	310	589
Dehumidifying Volume (Pint/Day)	71	71	116.7
Refrigerant Charge (Ounce)	R22 / 26.81 OZ	R22 / 34.57 OZ	R22 / 34.92 OZ
Dimension (W/D/H)(inch)	22.6" X 23.62" X 15.31"	22.6" X 23.62" X 15.31"	25.98" X 30.51" X 16.85"
Dimension of Package (W/D/H)(inch)	25.79" X 27.40" X 16.54"	25.79" X 27.40" X 16.54"	29.29" X 36.22" X 19.69"
Net Weight /Gross Weight (lbs)	97/114.6	97/114.6	165.3 / 183
Sound Pressure Level dB (A) (H/M/L)	58/53	58/56/53	59/53